MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES

STATE PUBLIC HEALTH LABORATORY

BREATH ALCOHOL PROGRAM

INTOX DMT MAINTENANCE REPORT

RECEIVED

REPORT #1

PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 EXPIRATION DATE 03/31/2017 TELEPHONE NUMBER 573-426-3860	Complete this report at the time Complete this report whenever	the instrument is se	erviced or repaired a	id wheneve	rit is placed into		11 05, 2016	
SOUZ28	I	opy within 15 days	to the Breath Alcoho	l Program,	DHSS.			
19-28-16	500228 Phelps County Sheriff's Dept							
Values where determined.) Unmarked items must be corrected before using instrument. ☑ DIAGNOSTIC RECORD □ DATE AND TIME _09/30/2016 19:28:18 □ DETECTOR ☑ PROGRAM □ FILTER 1 ☑ SAMPLE CHAMBER _48.8°C □ FILTER 2 ☑ BREATH TUBE _48.1°C □ FILTER 2 ☑ PUMP □ INTERNAL STANDARD ☑ SIMULATOR STANDARD ☑ STANDARD SUPPLIER _GUTH □ LOT # 14220 □ EXP. DATE _09/24/2016 ☑ SIMULATOR TEMP (34°C ± 0.2°C) _34.0 □ SIMULATOR SN _SD1313 □ SIMULATOR EXP DATE _02/08/2017 ☑ CALIBRATION CHECK _ CONLY ONE STANDARD SID DE USED PER MAINTENANCE REPORT) ☑ CALIBRATION CHECK _ CONLY ONE STANDARD SID DE USED PER MAINTENANCE REPORT) ☑ O.10% STANDARD - MUST READ BETWEEN 0.076% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.076% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.076% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.076% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.076% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.076% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.076% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.076% AND 0.044% INCLUSIVE □ 0.09% STANDARD - MUST READ BETWEEN 0.076% A	LOCATION OF INSTRUMENT (STREET AND 500 W 2nd, Rolla, MO 654	city) 01						
DATE AND TIME 06/30/2016 19:28:18	CHECKLIST: Place a mark in t values where determined). Unm	he box by each iten arked items must b	n if found to be satist be corrected before u	actory or is	operating withir nent.	n established limits	. (Write in observed	
© PROGRAM © FILTER 1 © SAMPLE CHAMBER 48.8°C © FILTER 2 © BREATH TUBE 48.1°C © FILTER 3 © PUMP © INTERNAL STANDARD BREATH ANALYZER ACCURACY STANDARDS © SIMULATOR STANDARD © STANDARD SUPPLIER GUTH LOT # 14220 EXP. DATE 09/24/2016 © SIMULATOR TEMP (34°C±0.2°C) 34.0 © SIMULATOR STANDARD SIMULATOR SN SD1313 SIMULATOR EXP DATE 02/08/2017 © CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard All three tests must be within ±5% on the standard value and must have a spread of 005 or less. Mark the box corresponding to the standard being used. © 0.08% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.055% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.055%	☑ DIAGNOSTIC RECORD							
© SAMPLE CHAMBER 48.8°C	DATE AND TIME 06/30/2	2016 19:28:18		X DETE	CTOR			
© BREATH TUBE 48.1°C	☑ PROGRAM		☑ FILTER 1					
Description	SAMPLE CHAMBER _4	☑ FILTER 2						
BREATH ANALYZER ACCURACY STANDARDS SIMULATOR STANDARD COMPRESSED ETHANOL-GAS MIXTURE STANDARD SUPPLIER GUTH LOT # 14220 EXP. DATE 09/24/2016 SIMULATOR TEMP (34°° ± 0.2°C) 34.0 SIMULATOR SN _SD1313 SIMULATOR EXP DATE 02/08/2017 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used. SO 10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE 0.08% STANDARD - MUST READ BETWEEN 0.095% AND 0.084% INCLUSIVE 1 0.08% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 2 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.04% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.05% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.05% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.05% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.05% STANDARD - MUST READ BETWEEN 0.095% AND 0.042% INCLUSIVE 1 0.05% STANDARD - MUST READ BE	☐ BREATH TUBE 48.1°	☑ FILTER 3						
SIMULATOR STANDARD □ COMPRESSED ETHANOL-GAS MIXTURE □ STANDARD SUPPLIER GUTH LOT # 14220 EXP. DATE 09/24/2016 □ SIMULATOR TEMP (34°C ± 0.2°C) 34.0 SIMULATOR SN SD1313 SIMULATOR EXP DATE 02/08/2017 □ CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used. □ 0.10% STANDARD - MUST READ BETWEEN 0.099% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.038% AND 0.084% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDAR	☑ PUMP			☑ INTERNAL STANDARD				
S STANDARD SUPPLIER GUTH LOT # _14220 EXP. DATE _09/24/2016 SIMULATOR TEMP (34°C ± 0.2°C) _34.0 SIMULATOR SN _SD1313 SIMULATOR EXP DATE _02/08/2017 CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used. □ 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE TEST 1: 0.099 □ TEST 2: 0.100 □ TEST 3: 0.101 □ PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0 □ 0.04: 0 □ 0.0509: 1 □ 1014: 0 □ 1519: 1 □ OVER .19: 1 □ UST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN STAULISHED LIMITS (USE OTHER SIDE IF NECESSARY) INSPECTING OFFICER SIGNATURE □ PRINT FULL NAME PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 RETURN COMPLETED REPORT TO THE Breath Alond Program, MO Department of Health and Senior Services Southeast District Office	BREATH ANALYZER ACCUR	ACY STANDARD	S					
SIMULATOR TEMP (34°C±0.2°C) 34.0 SIMULATOR SN SD1313 SIMULATOR EXP DATE 02/08/2017 □ CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used. □ 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 1.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 1.0509 □ TEST 2: 0.100 □ TEST 3: 0.101 □ PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0 0.04: 0 0.0509: 1 1014: 0 1519: 1 0VER .19: 1 UIST ANY NEW PARTIS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILLY AND WITHIN STANDARD	☑ SIMULATOR STANDARD [☐ COMPRESSED ETHANOL-GAS MIXTURE			
© CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used. © 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE TEST 1: 0.099 □ TEST 2: 0.100 □ TEST 3: 0.101 □ PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0 □ 0.4: 0 □ 0.509: 1 □ 1014: 0 □ 1519: 1 □ OVER .19: 1 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN STABLISHED LIMITS (USE OTHER SIDE IF NECESSARY) INSPECTING OFFICER SIGNATURE □ PRINT FULL NAME PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 RETURN COMPLETED REPORT TO THE Breath Oldon Program, MO Department of Health and Senior Services Southeast District Office	STANDARD SUPPLIER G	LOT#_ <u>14220</u>			EXP. DATE <u>09/24/2016</u>			
Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of .005 or less. Mark the box corresponding to the standard being used. © 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE © 0.08% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE © 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE TEST 1: 0.099 TEST 2: 0.100 TEST 3: 0.101 © PERFORM R.F.I. TEST INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0	☑ SIMULATOR TEMP (34°C:	± 0,2°C) 34.0	SIMUL	ATOR SN_	<u>SD1313</u> S	IMULATOR EXP	DATE <u>02/08/2017</u>	
INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0	☑ 0.10% STANDARE ☐ 0.08% STANDARE	- MUST READ BE - MUST READ BE	ETWEEN 0.095% AI ETWEEN 0.076% AI	ND 0.105% ND 0.084%	INCLUSIVE			
INDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT: REFUSALS: 0 004: 0 .0509: 1 .1014: 0 .1519: 1 .0VER .19: 1 LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY) INSPECTING OFFICER SIGNATURE SIGNATURE PRINT FULL NAME PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 EXPIRATION DATE 03/31/2017 TELEPHONE NUMBER 250072 RETURN COMPLETED REPORT TO THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office	TEST 1: 0,099	TEST 2: 0.100			TEST 3: 0.101			
REFUSALS: 0	☑ PERFORM R.F.I. TEST					·		
LIST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN ESTABLISHED LIMITS (USE OTHER SIDE IF NECESSARY) INSPECTING OFFICER SIGNATURE SIGNATURE PRINT FULL NAME PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 EXPIRATION DATE 03/31/2017 TELEPHONE NUMBER 250072 RETURN COMPLETED REPORT TO THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office	INDICATE THE NUMBER OF	BREATH TESTS	IN THE FOLLOWI	NG RANG	ES SINCE THE	LAST MAINTEN	NANCE REPORT:	
INSPECTING OFFICER SIGNATURE SIGNATURE TYPE II PERMIT NUMBER 250072 RETURN COMPLETED REPORT TO THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office	REFUSALS: 0 004: ()	0509: 1	.1014:	0	.1519: 1	OVER .19: 1	
PRINT FULL NAME PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 EXPIRATION DATE 03/31/2017 FOR THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office			CATION THAT WAS MADE TO	O RESTORE TH	E INSTRUMENT TO O	PERATE SATISFACTORIL	Y AND WITHIN	
PRINT FULL NAME PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 EXPIRATION DATE 03/31/2017 FOR THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office		<u></u>						
PRINT FULL NAME PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 EXPIRATION DATE 03/31/2017 FOR THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office								
PRINT FULL NAME PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 EXPIRATION DATE 03/31/2017 FOR THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office								
PRINT FULL NAME PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 EXPIRATION DATE 03/31/2017 FOR THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office								
PRINT FULL NAME PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 EXPIRATION DATE 03/31/2017 FOR THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office								
PAUL J LAMBERT TYPE II PERMIT NUMBER 250072 EXPIRATION DATE 03/31/2017 TELEPHONE NUMBER 573-426-3860 RETURN COMPLETED REPORT TO THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office				DOINT ELLI	NAME			
250072 03/31/2017 573-426-3860 RETURN COMPLETED REPORT TO THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office								
Southeast District Office								
	RETURN COMPLETED REPO	Soi	utheast District Office	•		n and Senior Servi	ces	



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



PERMIT TYPE II

PAUL J LAMBERT

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs,

and operate the following breath analyzer(s):

DATAMASTER, INTOX DMT

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

DATE 3/31/2015

DIRECTOR OF STATE PUBLIC HEALTH LABORATORY

NUMBER 250072

EXPIRES 3/31/2017

DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

MO 580-07-146-101

LAE-4 (HS-10)





CERTIFICATE OF ANALYSIS

Certified Alcohol Reference Solution for Simulator

Random Samples of Lot Number 14220 of Alcohol Reference Solution for Simulator were analyzed by gas chromatography on September 25, 2014, using a Perkin Elmer Gas Chromatograph Autosystem XL S/N: 610N9030209, and found to contain 0.1209% (w/vol) ethyl alcohol. The expiration date for this lot number is September 24, 2016 at 11:59 PM.

When used in a calibrated Simulator, operating at 34°C +/- .2°C, this solution will give a breath alcohol analysis instrument reading of 0.100 g/210L +/- 3%.

The alcohol and water used in this solution were free of test interfering substances.

Ted L. Pauley, President GUTH LABORATORIES, INC.

NIST Traceability:

Testing was conducted using Cerilliant Reference Standard lot number FN08051301 whose values are traceable to NIST.

All balances are calibrated annually by an outside agency using NIST traceable weights. Calibration verification is done prior to each use utilizing NIST traceable weights.